

CVS/Caremark

Implementation Guide

852 – Product Activity Data
Point of Sale

Version X12-4010

Table of Contents

852	Product Activity Data	1
ST	Transaction Set Header	2
XQ	Reporting Date/Action	3
N9	Reference Identification	4
N1	Loop Name	5
N1	Name	6
LIN	Loop Item Identification.....	7
LIN	Item Identification	8
PO4	Item Physical Details.....	9
ZA	Loop Product Activity Reporting	10
ZA	Product Activity Reporting	11
CTP	Pricing Information	12
SDQ	Destination Quantity	13
CTT	Transaction Totals	16
SE	Transaction Set Trailer	17

852

Product Activity Data**Functional Group=PD**

Purpose: This Draft Standard for Trial Use contains the format and establishes the data contents of the Product Activity Data Transaction Set (852) for use within the context of an Electronic Data Interchange (EDI) environment. The transaction set can be used by a distributor, warehouse, or retailer to advise a trading partner of inventory, sales, and other product activity information. Product activity data enables a trading partner to plan and ship, or propose inventory replenishment quantities, for distribution centers, warehouses or retail outlets. The receiver of the transaction set will maintain some type of inventory/product movement records for its trading partners to enable replenishment calculations based on data provided by the distributor, warehouse or retailer.

Heading:

<u>Pos</u>	<u>Id</u>	<u>Segment Name</u>	<u>Req</u>	<u>Max Use</u>	<u>Repeat</u>	<u>Notes</u>	<u>Usage</u>
010	ST	Transaction Set Header	M	1			Must use
020	XQ	Reporting Date/Action	M	1			Must use
040	N9	Reference Identification	O	>1			Must use
<u>LOOP ID - N1</u>					<u>200</u>	<u>N1/060L</u>	
060	N1	Name	O	1		N1/060	Must use

Detail:

<u>Pos</u>	<u>Id</u>	<u>Segment Name</u>	<u>Req</u>	<u>Max Use</u>	<u>Repeat</u>	<u>Notes</u>	<u>Usage</u>
<u>LOOP ID - LIN</u>					<u>999999</u>		
010	LIN	Item Identification	O	1			Must use
030	PO4	Item Physical Details	O	1			Must use
<u>LOOP ID - ZA</u>					<u>≥1</u>	<u>N2/080L</u>	
080	ZA	Product Activity Reporting	M	1		N2/080	Must use
100	CTP	Pricing Information	O	25			Must use
110	SDQ	Destination Quantity	O	>1			Must use

Summary:

<u>Pos</u>	<u>Id</u>	<u>Segment Name</u>	<u>Req</u>	<u>Max Use</u>	<u>Repeat</u>	<u>Notes</u>	<u>Usage</u>
010	CTT	Transaction Totals	O	1		N3/010	Must use
020	SE	Transaction Set Trailer	M	1			Must use

Notes:

- 1/060L The reporting location is required. The reporting location is specified explicitly in the N1 segment using the code RL in N101, or implicitly using the SDQ segment (Table 2) with the location data elements. They are mutually exclusive (the SDQ and the N1 with N101 containing RL).
- 1/060 The reporting location is required. The reporting location is specified explicitly in the N1 segment using the code RL in N101, or implicitly using the SDQ segment (Table 2) with the location data elements. They are mutually exclusive (the SDQ and the N1 with N101 containing RL).
- 2/080L The quantity for the item identified in the LIN segment is required. Quantity is specified either in the ZA segment (ZA02) or in the SDQ segment.
- 2/080 The quantity for the item identified in the LIN segment is required. Quantity is specified either in the ZA segment (ZA02) or in the SDQ segment.
- 3/010 The number of line items (CTT01) is the accumulation of the number of LIN segments. Hash total (CTT02) is not used in this transaction set. When sending item and activity data in the LIN loop, the CTT segment is required.

ST Transaction Set Header

Pos: 010	Max: 1
Heading - Mandatory	
Loop: N/A	Elements: 2

User Option (Usage): Must use

Purpose: To indicate the start of a transaction set and to assign a control number

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
ST01	143	Transaction Set Identifier Code	M	ID	3/3	Must use

Description: Code uniquely identifying a Transaction Set

CodeList Summary (Total Codes: 298, Included: 1)

<u>Code</u>	<u>Name</u>
852	Product Activity Data

ST02	329	Transaction Set Control Number	M	AN	4/9	Must use
------	-----	--------------------------------	---	----	-----	----------

Description: Identifying control number that must be unique within the transaction set functional group assigned by the originator for a transaction set

Semantics:

1. The transaction set identifier (ST01) used by the translation routines of the interchange partners to select the appropriate transaction set definition (e.g., 810 selects the Invoice Transaction Set).

XQ**Reporting Date/Action**

Pos: 020	Max: 1
Heading - Mandatory	
Loop: N/A	Elements: 3

User Option (Usage): Must use**Purpose:** To specify reporting date and action to be taken**Element Summary:**

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
XQ01	305	Transaction Handling Code	M	ID	1/2	Must use

Description: Code designating the action to be taken by all parties**CodeList Summary** (Total Codes: 23, Included: 1)

<u>Code</u>	<u>Name</u>
H	Notification Only

XQ02	373	Date	M	DT	8/8	Must use
------	-----	------	---	----	-----	----------

Description: Date expressed as CCYYMMDD
Start Date - Begin Date of Reporting Period

XQ03	373	Date	O	DT	8/8	Must use
------	-----	------	---	----	-----	----------

Description: Date expressed as CCYYMMDD
End Date – Ending Date of Reporting Period**Semantics:**

1. XQ02 is the reporting date. If reporting a date range, then XQ02 is the start date and XQ03 is the end date.

N9**Reference Identification**

Pos: 040	Max: >1
Heading - Optional	
Loop: N/A	Elements: 2

User Option (Usage): Must use**Purpose:** To transmit identifying information as specified by the Reference Identification Qualifier**Element Summary:**

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
N901	128	Reference Identification Qualifier	M	ID	2/3	Must use

Description: Code qualifying the Reference Identification**CodeList Summary** (Total Codes: 1503, Included: 1)

<u>Code</u>	<u>Name</u>
VR	Vendor ID Number

N902	127	Reference Identification	X	AN	1/30	Must use
------	-----	---------------------------------	---	----	------	----------

Description: Reference information as defined for a particular Transaction Set or as specified by the Reference Identification Qualifier

Vendor Number Assigned by CVS

Syntax Rules:

1. R0203 - At least one of N902 or N903 is required.
2. C0605 - If N906 is present, then N905 is required.

Semantics:

1. N906 reflects the time zone which the time reflects.
2. N907 contains data relating to the value cited in N902.

Loop Name

Pos: 060	Repeat: 200
Optional	
Loop: N1	Elements: N/A

User Option (Usage): Must use

Purpose: To identify a party by type of organization, name, and code

Loop Summary:

<u>Pos</u>	<u>Id</u>	<u>Segment Name</u>	<u>Req</u>	<u>Max Use</u>	<u>Repeat</u>	<u>Usage</u>
060	N1	Name	O	1		Must use

N1**Name**

Pos: 060	Max: 1
Heading - Optional	
Loop: N1	Elements: 2

User Option (Usage): Must use**Purpose:** To identify a party by type of organization, name, and code**Element Summary:**

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
N101	98	Entity Identifier Code	M	ID	2/3	Must use

Description: Code identifying an organizational entity, a physical location, property or an individual**CodeList Summary** (Total Codes: 1312, Included: 1)

<u>Code</u>	<u>Name</u>
RL	Reporting Location

N102	93	Name	X	AN	1/60	Must use
------	----	------	---	----	------	----------

Description: Free-form name**Syntax Rules:**

1. R0203 - At least one of N102 or N103 is required.
2. P0304 - If either N103 or N104 is present, then the other is required.

Comments:

1. This segment, used alone, provides the most efficient method of providing organizational identification. To obtain this efficiency the "ID Code" (N104) must provide a key to the table maintained by the transaction processing party.
2. N105 and N106 further define the type of entity in N101.

Loop Item Identification

Pos: 010	Repeat: 999999
	Optional
Loop: LIN	Elements: N/A

User Option (Usage): Must use

Purpose: To specify basic item identification data

Loop Summary:

<u>Pos</u>	<u>Id</u>	<u>Segment Name</u>	<u>Req</u>	<u>Max Use</u>	<u>Repeat</u>	<u>Usage</u>
010	LIN	Item Identification	O	1		Must use
030	PO4	Item Physical Details	O	1		Must use
080		Loop ZA	M		>1	Must use

LIN Item Identification

Pos: 010	Max: 1
Detail - Optional	
Loop: LIN	Elements: 2

User Option (Usage): Must use

Purpose: To specify basic item identification data

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
LIN02	235	Product/Service ID Qualifier	M	ID	2/2	Must use

Description: Code identifying the type/source of the descriptive number used in Product/Service ID (234)

CodeList Summary (Total Codes: 477, Included: 1)

<u>Code</u>	<u>Name</u>
UI	U.P.C. Consumer Package Code (1-5-5)
UD	U.P.C/EAN Consumer Package Code (2-5-5)
ND	If RX – ND (NDC)

LIN03	234	Product/Service ID	M	AN	1/48	Must use
-------	-----	--------------------	---	----	------	----------

Description: Identifying number for a product or service

Item UPC Number
EAN
If RX – NDC

Syntax Rules:

1. P0405 - If either LIN04 or LIN05 is present, then the other is required.
2. P0607 - If either LIN06 or LIN07 is present, then the other is required.
3. P0809 - If either LIN08 or LIN09 is present, then the other is required.
4. P1011 - If either LIN10 or LIN11 is present, then the other is required.
5. P1213 - If either LIN12 or LIN13 is present, then the other is required.
6. P1415 - If either LIN14 or LIN15 is present, then the other is required.
7. P1617 - If either LIN16 or LIN17 is present, then the other is required.
8. P1819 - If either LIN18 or LIN19 is present, then the other is required.
9. P2021 - If either LIN20 or LIN21 is present, then the other is required.
10. P2223 - If either LIN22 or LIN23 is present, then the other is required.
11. P2425 - If either LIN24 or LIN25 is present, then the other is required.
12. P2627 - If either LIN26 or LIN27 is present, then the other is required.
13. P2829 - If either LIN28 or LIN29 is present, then the other is required.
14. P3031 - If either LIN30 or LIN31 is present, then the other is required.

Semantics:

1. LIN01 is the line item identification

Comments:

1. See the Data Dictionary for a complete list of IDs.
2. LIN02 through LIN31 provide for fifteen different product/service IDs for each item. For example: Case, Color, Drawing No., U.P.C. No., ISBN No., Model No., or SKU.

PO4 Item Physical Details

Pos: 030	Max: 1
Detail - Optional	
Loop: LIN	Elements: 1

User Option (Usage): Must use

Purpose: To specify the physical qualities, packaging, weights, and dimensions relating to the item

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
PO401	356	Pack	O	N0	1/6	Must use

Description: The number of inner containers, or number of eaches if there are no inner containers, per outer container

P.O. Case Pack

Syntax Rules:

1. P0203 - If either PO402 or PO403 is present, then the other is required.
2. C0506 - If PO405 is present, then PO406 is required.
3. P0607 - If either PO406 or PO407 is present, then the other is required.
4. P0809 - If either PO408 or PO409 is present, then the other is required.
5. C1013 - If PO410 is present, then PO413 is required.
6. C1113 - If PO411 is present, then PO413 is required.
7. C1213 - If PO412 is present, then PO413 is required.
8. L13101112 - If PO413 is present, then at least one of PO410, PO411 or PO412 is required.
9. C1716 - If PO417 is present, then PO416 is required.
10. C1804 - If PO418 is present, then PO404 is required.

Semantics:

1. PO415 is used to indicate the relative layer of this package or range of packages within the layers of packaging. Relative Position 1 (value R1) is the innermost package.
2. PO416 is the package identifier or the beginning package identifier in a range of identifiers.
3. PO417 is the ending package identifier in a range of identifiers.
4. PO418 is the number of packages in this layer.

Comments:

1. PO403 - The "Unit or Basis for Measure Code" in this segment position is for purposes of defining the pack (PO401) /size (PO402) measure which indicates the quantity in the inner pack unit. For example: If the carton contains 24 12-Ounce packages, it would be described as follows: Data element 356 = "24"; Data element 357 = "12"; Data element 355 = "OZ".
2. PO413 defines the unit of measure for PO410, PO411, and PO412.

Loop Product Activity Reporting

Pos: 080	Repeat: >1
Mandatory	
Loop: ZA	Elements: N/A

User Option (Usage): Must use

Purpose: To provide activity details concerning product being reported

Loop Summary:

<u>Pos</u>	<u>Id</u>	<u>Segment Name</u>	<u>Req</u>	<u>Max Use</u>	<u>Repeat</u>	<u>Usage</u>
080	ZA	Product Activity Reporting	M	1		Must use
100	CTP	Pricing Information	O	25		Must use
110	SDQ	Destination Quantity	O	>1		Must use

ZA**Product Activity Reporting**

Pos: 080	Max: 1
Detail - Mandatory	
Loop: ZA	Elements: 1

User Option (Usage): Must use**Purpose:** To provide activity details concerning product being reported**Element Summary:**

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
ZA01	859	Activity Code	M	ID	2/2	Must use

Description: Code identifying activity details for the product being reported**CodeList Summary** (Total Codes: 39, Included: 2)

<u>Code</u>	<u>Name</u>
QD	Additional Demand Quantity – Promotional/Seasonal quantity
QS	Quantity Sold – Regular quantity

Syntax Rules:

1. P0203 - If either ZA02 or ZA03 is present, then the other is required.
2. P0405 - If either ZA04 or ZA05 is present, then the other is required.
3. P0607 - If either ZA06 or ZA07 is present, then the other is required.

Semantics:

1. ZA08 determines if the product activity code in ZA01 refers to a product that is categorized as In-bond merchandise. A "Y" indicates that the activity code applies to a product that is In-bond; an "N" indicates that the activity code does not refer to a product that is In-bond.

CTP Pricing Information

Pos: 100	Max: 25
Detail - Optional	
Loop: ZA	Elements: 2

User Option (Usage): Must use

Purpose: To specify pricing information

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
CTP02	236	Price Identifier Code	X	ID	3/3	Must use
Description: Code identifying pricing specification						
CodeList Summary (Total Codes: 164, Included: 1)						
<u>Code</u>	<u>Name</u>					
UCP	Unit cost price					
CTP03	212	Unit Price	X	R	1/17	Must use
Description: Price per unit of product, service, commodity, etc						
Unit cost price.						

Syntax Rules:

1. P0405 - If either CTP04 or CTP05 is present, then the other is required.
2. C0607 - If CTP06 is present, then CTP07 is required.
3. C0902 - If CTP09 is present, then CTP02 is required.
4. C1002 - If CTP10 is present, then CTP02 is required.
5. C1103 - If CTP11 is present, then CTP03 is required.

Semantics:

1. CTP07 is a multiplier factor to arrive at a final discounted price. A multiplier of .90 would be the factor if a 10% discount is given.
2. CTP08 is the rebate amount.

Comments:

1. See Figures Appendix for an example detailing the use of CTP03 and CTP04.
2. See Figures Appendix for an example detailing the use of CTP03, CTP04 and CTP07.

SDQ Destination Quantity

Pos: 110	Max: >1
Detail - Optional	
Loop: ZA	Elements: 22

User Option (Usage): Must use

Purpose: To specify destination and quantity detail

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
SDQ01	355	Unit or Basis for Measurement Code	M	ID	2/2	Must use
Description: Code specifying the units in which a value is being expressed, or manner in which a measurement has been taken						
CodeList Summary (Total Codes: 794, Included: 1)						
		<u>Code</u>		<u>Name</u>		
		PC		Piece		
SDQ02	66	Identification Code Qualifier	O	ID	1/2	Must use
Description: Code designating the system/method of code structure used for Identification Code (67)						
CodeList Summary (Total Codes: 215, Included: 1)						
		<u>Code</u>		<u>Name</u>		
		FA		Facility Identification		
SDQ03	67	Identification Code	M	AN	2/80	Must use
Description: Code identifying a party or other code						
		Store Number				
SDQ04	380	Quantity	M	R	1/15	Must use
Description: Numeric value of quantity						
		Quantity				
SDQ05	67	Identification Code	X	AN	2/80	Used
Description: Code identifying a party or other code						
		Store Number				
SDQ06	380	Quantity	X	R	1/15	Used
Description: Numeric value of quantity						
		Quantity				
SDQ07	67	Identification Code	X	AN	2/80	Used
Description: Code identifying a party or other code						
		Store Number				
SDQ08	380	Quantity	X	R	1/15	Used
Description: Numeric value of quantity						
		Quantity				
SDQ09	67	Identification Code	X	AN	2/80	Used
Description: Code identifying a party or other code						
		Store Number				
SDQ10	380	Quantity	X	R	1/15	Used
Description: Numeric value of quantity						
		Quantity				
SDQ11	67	Identification Code	X	AN	2/80	Used
Description: Code identifying a party or other code						
		Store Number				

SDQ12	380	Quantity Description: Numeric value of quantity Quantity	X	R	1/15	Used
SDQ13	67	Identification Code Description: Code identifying a party or other code Store Number	X	AN	2/80	Used
SDQ14	380	Quantity Description: Numeric value of quantity Quantity	X	R	1/15	Used
SDQ15	67	Identification Code Description: Code identifying a party or other code Store Number	X	AN	2/80	Used
SDQ16	380	Quantity Description: Numeric value of quantity Quantity	X	R	1/15	Used
SDQ17	67	Identification Code Description: Code identifying a party or other code Store Number	X	AN	2/80	Used
SDQ18	380	Quantity Description: Numeric value of quantity Quantity	X	R	1/15	Used
SDQ19	67	Identification Code Description: Code identifying a party or other code Store Number	X	AN	2/80	Used
SDQ20	380	Quantity Description: Numeric value of quantity Quantity	X	R	1/15	Used
SDQ21	67	Identification Code Description: Code identifying a party or other code Store Number	X	AN	2/80	Used
SDQ22	380	Quantity Description: Numeric value of quantity Quantity	X	R	1/15	Used

Syntax Rules:

- 1.P0506 - If either SDQ05 or SDQ06 is present, then the other is required.
- 2.P0708 - If either SDQ07 or SDQ08 is present, then the other is required.
- 3.P0910 - If either SDQ09 or SDQ10 is present, then the other is required.
- 4.P1112 - If either SDQ11 or SDQ12 is present, then the other is required.
- 5.P1314 - If either SDQ13 or SDQ14 is present, then the other is required.
- 6.P1516 - If either SDQ15 or SDQ16 is present, then the other is required.
- 7.P1718 - If either SDQ17 or SDQ18 is present, then the other is required.
- 8.P1920 - If either SDQ19 or SDQ20 is present, then the other is required.
- 9.P2122 - If either SDQ21 or SDQ22 is present, then the other is required.

Semantics:

1. SDQ23 identifies the area within the location identified in SDQ03, SDQ05, SDQ07, SDQ09, SDQ11, SDQ13, SDQ15, SDQ17, SDQ19, and SDQ21.

Comments:

1. SDQ02 is used only if different than previously defined in the transaction set.
2. SDQ03 is the store number.
3. SDQ23 may be used to identify areas within a store, e.g., front room, back room, selling outpost, end aisle display, etc. The value is agreed to by trading partners or industry conventions.

CTT Transaction Totals

Pos: 010	Max: 1
Summary - Optional	
Loop: N/A	Elements: 2

User Option (Usage): Must use

Purpose: To transmit a hash total for a specific element in the transaction set

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
CTT01	354	Number of Line Items	M	N0	1/6	Must use

Description: Total number of line items in the transaction set
 Number of Line Items (Count of LIN Segments)

CTT02	347	Hash Total	O	R	1/10	Must use
		Quantity Total				

Description: Sum of values of the specified data element. All values in the data element will be summed without regard to decimal points (explicit or implicit) or signs. Truncation will occur on the left most digits if the sum is greater than the maximum size of the hash total of the data element.
 Example: -.0018 First occurrence of value being hashed. .18 Second occurrence of value being hashed. 1.8 Third occurrence of value being hashed. 18.01 Fourth occurrence of value being hashed.
 ----- 1855 Hash total prior to truncation. 855 Hash total after truncation to three-digit field.

Syntax Rules:

- 1.P0304 - If either CTT03 or CTT04 is present, then the other is required.
- 2.P0506 - If either CTT05 or CTT06 is present, then the other is required.

Comments:

1. This segment is intended to provide hash totals to validate transaction completeness and correctness.

SE Transaction Set Trailer

Pos: 020	Max: 1
Summary - Mandatory	
Loop: N/A	Elements: 2

User Option (Usage): Must use

Purpose: To indicate the end of the transaction set and provide the count of the transmitted segments (including the beginning (ST) and ending (SE) segments)

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
SE01	96	Number of Included Segments	M	N0	1/10	Must use
Description: Total number of segments included in a transaction set including ST and SE segments						
SE02	329	Transaction Set Control Number	M	AN	4/9	Must use
Description: Identifying control number that must be unique within the transaction set functional group assigned by the originator for a transaction set						

Comments:

1. SE is the last segment of each transaction set.

852 – Point of Sale Example v4010:

ISA*00* *00* *ZZ*CVS *ZZ*Vendor ID *120531*0416*U*00400*000000240*0*P*^~
 GS*PD*CVS* Vendor ID*20120531*0416*15*X*004010~
 ST*852*0016~
 XQ*H*20120520*20120526~
 N9*VR*19999~
 N1*RL*CVS~
 LIN**UI*99999999999~
 PO4*24~
 ZA*QS~
 CTP**UCP*24.49~
 SDQ*PC*FA*04829*1~
 ZA*QD~
 CTP**UCP*24.49~
 SDQ*PC*FA*04902*1*05315*1*06704*1*06918*1*08605*1~
 ZA*QD~
 CTP**UCP*24.99~
 SDQ*PC*FA*00273*1*00668*1*01268*1~
 ZA*QS~
 CTP**UCP*24.99~
 SDQ*PC*FA*02732*1~
 ZA*QD~
 CTP**UCP*24.99~
 SDQ*PC*FA*03174*1*03263*1*04249*1*04540*1*05906*1*06238*1*07179*1*07443*1*07645*1*08141*1~
 SDQ*PC*FA*08309*1*08389*1*08614*1*08740*1*08772*1*09580*1*09691*1*09717*1~
 ZA*QD~
 CTP**UCP*25.49~
 SDQ*PC*FA*00049*1*00718*1*01169*1*01415*1*06852*1*07460*1*08378*1*09264*1*09479*1~
 ZA*QD~
 CTP**UCP*25.79~
 SDQ*PC*FA*00144*1*00233*1*00692*1*00802*1*01258*1*02325*1*02550*1*02951*1*03788*1*04455*1~
 ZA*QS~
 CTP**UCP*25.79~
 SDQ*PC*FA*04605*1~
 ZA*QD~
 CTP**UCP*25.79~
 SDQ*PC*FA*05112*1*07701*1*09684*1~
 ZA*QD~
 CTP**UCP*25.99~
 SDQ*PC*FA*00506*1*02835*1*05191*1*09187*1*09235*1*09242*1~
 ZA*QD~
 CTP**UCP*26.99~
 SDQ*PC*FA*00381*1*00716*1*00984*1*00991*1*02168*1*02457*1*02940*1*08900*1~
 ZA*QD~
 CTP**UCP*35.28~
 SDQ*PC*FA*08340*2~
 ZA*QD~
 CTP**UCP*35.98~
 SDQ*PC*FA*04081*2*05800*2*07969*2~
 ZA*QD~
 CTP**UCP*39.98~

SDQ*PC*FA*00009*2*00026*2*00146*2*00219*2*00298*2*00300*2*00343*2*00415*2*00432*2*00494*2~
 SDQ*PC*FA*00524*2*00632*2*00642*2*00668*2*00693*2*00704*2*00765*2*00810*2*00835*2*00905*2~
 SDQ*PC*FA*00918*2*00929*2*01001*2*01003*2*01004*2*01088*2*01166*2*01185*2*01219*2*01220*2~
 SDQ*PC*FA*01256*2*01280*2*01311*2*01321*2*01339*2*01385*2*01389*2*01411*2*01416*
 2*01429*2~
 ZA*QS~
 CTP**UCP*50.98~
 SDQ*PC*FA*00763*2~
 ZA*QD~
 CTP**UCP*53.97~
 SDQ*PC*FA*04594*3~
 ZA*QD~
 CTP**UCP*53.98~
 SDQ*PC*FA*02671*2~
 ZA*QD~
 CTP**UCP*59.97~
 SDQ*PC*FA*00217*3*00465*3*00814*3*01055*3*01098*3*01103*3*02430*3*02735*3*03023*3*03224*3~
 SDQ*PC*FA*03752*3*04017*3*05059*3*05253*3*05703*3*06252*3*06553*3*06647*3*07092*3*07190*3~
 SDQ*PC*FA*07265*3*08837*3*08875*3*09370*3*09527*3*09652*3*09660*3*09721*3*09739*3*09778*3~
 ZA*QS~
 CTP**UCP*59.98~
 SDQ*PC*FA*03210*2~
 ZA*QD~
 CTP**UCP*79.96~
 SDQ*PC*FA*00915*4*01293*4*03204*4*03547*4*09903*4~
 ZA*QD~
 CTP**UCP*99.95~
 SDQ*PC*FA*01942*5*09575*5~
 ZA*QD~
 CTP**UCP*143.92~
 SDQ*PC*FA*05219*8~
 CTT*1*1854~
 SE*81*0016~
 GE*1*15~
 IEA*1*000000240~